

# TECHNICAL DATA SHEET



## WIKO® SUPER GLUE FILLER



## CYANOACRYLATE ADHESIVES ACCESSORIES

WIKO® SUPER GLUE FILLER is used to fill holes, gaps and cracks or to adjust surface irregularities in connection with the usage of WIKO® SUPER GLUE adhesives.

WIKO® SUPER GLUE FILLER can be used for all materials, like e.g. wood, steel, non-ferrous metals and plastics.

### Properties

|                         |                                                        |
|-------------------------|--------------------------------------------------------|
| Specific weight [kg/l]: | Approx. 2,45                                           |
| Hardness:               | Knoop 5150 N/mm <sup>2</sup> $\pm$ HRC 47 $\pm$ Mohs 6 |

### Sizes

The WIKO® SUPER GLUE FILLER is available in a 30 g bottle.

### Application

#### Option 1:

Fill the designated spot with WIKO® SUPER GLUE FILLER. Apply the CA adhesive onto the surface of the filler and allow time for the adhesive to cure.

#### Option 2:

Fill the designated spot with CA adhesives and quickly apply WIKO® SUPER GLUE FILLER onto the CA adhesives and allow time for the adhesive to cure.

### Storage & Durability

The shelf life is, at the optimum storage temperature of 0 °C to +40 °C in the closed original container, a maximum of 24 months. A higher storage temperature leads to a significantly lower durability. The storage temperature must not fall below 0 °C. Protect the product from direct sunlight or heat, frost and humidity.

### Safety data sheets

Please refer to the current data sheet for safety relevant data.  
Click or scan here:



#### Note:

Please note the information and notes in our respective safety data sheets. The data contained herein are for informational purposes only and are believed to be accurate to the best of our knowledge. We assume no liability for the results. For optimum functionality of the adhesive system, please only use the cartridge and mixer systems tested and released by GLUETEC. The product is only suitable for professional and experienced users. It is the user's own responsibility to take precautions to protect property and people from the hazards that may be encountered in handling and using these products. Accordingly, GLUETEC specifically disclaims any warranty, expressed or implied, including any warranty or suitability commitments for a particular purpose. In particular, GLUETEC disclaims all liability for consequential or indirect damages of any kind.